



**Application:** offices, shops, entrance halls, apartments

**Housing:** cast aluminum, painted


**Color:** grey RAL9006; white RAL9010;  
black RAL9005

**Source:** LED COB, operational durability of 50,000  
operating hours

**Durability:** L90B20

**McAdam:** <3

**Power supply:** electronic, inside the luminaire  
ON / OFF (standard); DALI



Ref. no.	Name	Power	Luminous flux	Beam angle	Luminous efficiency	CRI	Tb [K]	Weight
<b>32.0101.XX.YYY</b>	BERKIS R	5W	800lm	24°	157lm/W	>90	2700; 3000; 3500; 4000	1,00kg
<b>32.0102.XX.YYY</b>	BERKIS R	7W	1100lm	24°	136lm/W	>90	2700; 3000; 3500; 4000	1,00kg
<b>32.0103.XX.YYY</b>	BERKIS R	11W	1500lm	24°	143lm/W	>90	2700; 3000; 3500; 4000	1,00kg
<b>32.0111.XX.YYY</b>	BERKIS R	5W	800lm	36°	157lm/W	>90	2700; 3000; 3500; 4000	1,00kg
<b>32.0112.XX.YYY</b>	BERKIS R	7W	1100lm	36°	136lm/W	>90	2700; 3000; 3500; 4000	1,00kg
<b>32.0113.XX.YYY</b>	BERKIS R	11W	1500lm	36°	143lm/W	>90	2700; 3000; 3500; 4000	1,00kg
<b>32.0121.XX.YYY</b>	BERKIS R	5W	800lm	60°	157lm/W	>90	2700; 3000; 3500; 4000	1,00kg
<b>32.0122.XX.YYY</b>	BERKIS R	7W	1100lm	60°	136lm/W	>90	2700; 3000; 3500; 4000	1,00kg
<b>32.0123.XX.YYY</b>	BERKIS R	11W	1500lm	60°	143lm/W	>90	2700; 3000; 3500; 4000	1,00kg

