



Application: offices, shops, entrance halls, apartments

Housing: cast aluminum, painted

Color: grey RAL9006; white RAL9010;
black RAL9005

Source: LED COB, operational durability of 50,000
operating hours

Durability: L90B20

McAdam: <3

Power supply: electronic, inside the luminaire
ON / OFF (standard); DALI



Ref. no.	Name	Power	Luminous flux	Beam angle	Luminous efficiency	CRI	Tb [K]	Weight
32.0151.XX.YYY	BERKIS R	7W	1100lm	24°	157lm/W	>90	2700; 3000; 3500; 4000	1,95kg
32.0152.XX.YYY	BERKIS R	11W	1500lm	24°	136lm/W	>90	2700; 3000; 3500; 4000	1,95kg
32.0153.XX.YYY	BERKIS R	14W	2000lm	24°	143lm/W	>90	2700; 3000; 3500; 4000	1,95kg
32.0154.XX.YYY	BERKIS R	18W	2500lm	24°	139lm/W	>90	2700; 3000; 3500; 4000	1,95kg
32.0161.XX.YYY	BERKIS R	7W	1100lm	36°	157lm/W	>90	2700; 3000; 3500; 4000	1,95kg
32.0162.XX.YYY	BERKIS R	11W	1500lm	36°	136lm/W	>90	2700; 3000; 3500; 4000	1,95kg
32.0163.XX.YYY	BERKIS R	14W	2000lm	36°	143lm/W	>90	2700; 3000; 3500; 4000	1,95kg
32.0164.XX.YYY	BERKIS R	18W	2500lm	36°	139lm/W	>90	2700; 3000; 3500; 4000	1,95kg
32.0171.XX.YYY	BERKIS R	7W	1100lm	60°	157lm/W	>90	2700; 3000; 3500; 4000	1,95kg
32.0172.XX.YYY	BERKIS R	11W	1500lm	60°	136lm/W	>90	2700; 3000; 3500; 4000	1,95kg
32.0173.XX.YYY	BERKIS R	14W	2000lm	60°	143lm/W	>90	2700; 3000; 3500; 4000	1,95kg
32.0174.XX.YYY	BERKIS R	18W	2500lm	60°	139lm/W	>90	2700; 3000; 3500; 4000	1,95kg

