



Application: offices, shops, entrance lobbies, apartments

Housing: aluminum, painted structure, mat

Optics: Ledil lens

Color (XX):

white RAL9016 (01),

gray RAL9006 (02),

black RAL9005 (03)

RAL on request (RALXXXX)


Source (YYY): 830, 840; 930; 940

Lifetime: L90B20 50000h

Color rendering index CRI: > 80

Color temperature: 3000K; 4000K

Power supply: ON / OFF; DALI



Code	Power	Luminous flux	Light distribution	Efficacy	Control
04.019.0031.XX.YYY	12W	660lm	13°	55lm/W	ON/OFF
04.019.0032.XX.YYY	12W	840lm	44°	70lm/W	ON/OFF
04.019.0033.XX.YYY	12W	900lm	53°	75lm/W	ON/OFF
04.019.0034.XX.YYY	17W	940lm	13°	55lm/W	ON/OFF
04.019.0035.XX.YYY	17W	1200lm	44°	71lm/W	ON/OFF
04.019.0036.XX.YYY	17W	1300lm	53°	76lm/W	ON/OFF
04.019.0037.XX.YYY	26W	1300lm	13°	50lm/W	ON/OFF
04.019.0038.XX.YYY	26W	1650lm	44°	63lm/W	ON/OFF
04.019.0039.XX.YYY	26W	1750lm	53°	67lm/W	ON/OFF
04.019.0031.XX.YYY.DALI	12W	660lm	13°	55lm/W	DALI
04.019.0032.XX.YYY.DALI	12W	840lm	44°	70lm/W	DALI
04.019.0033.XX.YYY.DALI	12W	900lm	53°	75lm/W	DALI
04.019.0034.XX.YYY.DALI	17W	940lm	13°	55lm/W	DALI
04.019.0035.XX.YYY.DALI	17W	1200lm	44°	71lm/W	DALI
04.019.0036.XX.YYY.DALI	17W	1300lm	53°	76lm/W	DALI
04.019.0037.XX.YYY.DALI	26W	1300lm	13°	50lm/W	DALI
04.019.0038.XX.YYY.DALI	26W	1650lm	44°	63lm/W	DALI
04.019.0039.XX.YYY.DALI	26W	1750lm	53°	67lm/W	DALI

XX - luminaire colour

YYY - CRI/Tb

The data given in the table refer to LED 4000K CRI>90

last update: 2.11.2020

Spectra Lighting ul. Ostródzka 53 03-289 Warszawa tel.: +48 22 567 01 00 fax.: +48 22 567 01 01 e-mail: office@spectra-lighting.pl

